



General

Intumex® AN is an acrylic based, single component fire stopping sealant. Joints without movement can be sealed quickly thanks to its outstanding application qualities. A common emulsion paint can be used to colour the joints.

Area of Application

Intumex® AN is a fire stopping sealant for joints in walls and floors. It is designed for use with joints without movement to seal against the spread of smoke and fire.

System Advantage / Customer Benefit

- ⇒ Can be painted
- ⇒ Good adhesion to various substrates

Technical Data

| | |
|-----------------------|--|
| Colour | white/grey |
| Consistency | paste |
| Density | wet : 1.6 ± 0.2g/cm ³ trocken : 1.8 ± 0.2g/cm ³ |
| Solid Content | 86 ± 5 wght.% |
| Ash Content | approx. 70% (600°C, 15 minutes) |
| Movement Capabilities | elongation minimum 15% compression minimum 15% |

Test Certificate / Approval

- ⇒ EN 1366-4 (joints)
- ⇒ ÖNORM B 3807 (EN 13501-2/classification reports)
- ⇒ BS 476 Part 20 and 22

Packaging

- ⇒ 310ml cartridges, 25 tubes per carton, 1200 tubes/pallet
 - ⇒ 600ml foil packs upon request
 - ⇒ 16kg plastic buckets upon request
- Subject to change!

Storage Requirements

- ⇒ Store in cool and dry conditions
- ⇒ Protect from heat and frost
- ⇒ Shelf life of original sealed containers at least 12 months
- ⇒ Once opened, containers should be finished swiftly

Safety Instructions

- ⇒ Keep out of reach of children
- ⇒ Avoid contact with food and beverages
- ⇒ Please refer to the safety data sheet for additional advice

Intumex® products must be applied in accordance with EU directives and national regulations for construction material in general, and fire stopping in particular, with the applicable national test certificates and approvals, and in accordance with applicable national building regulations. Products may only be applied by trained professionals with adequate knowledge of and experience in the use of fire stopping products, and only after a thorough review of the installation guidelines, the safety data sheets, and the national test certificates and approvals. All the relevant documents can be obtained free-of-charge by contacting Intumex® or from your local dealer via telephone or in writing; in addition all installation guidelines and the safety data sheets can be downloaded free-of-charge from the Intumex® website (see www.intumex.at).