

## General

Intumex® FB is a permanently elastic intumescent brick, which is used to prevent the spread of smoke.

## Area of Application

Intumex® FB fire stopping is a brick shaped seal for walls and floors. It is designed to be used with cables, single or bundles, combustible and non-combustible pipes to seal against the spread of smoke and fire.



## System Advantages / Customer Benefits

- ⇒ permanently elastic
- ⇒ quick and easy, dust-free installation
- ⇒ easy retro-fitting of cables and plastic pipes

## Technical Data

Colour	dark grey
Density	approx. 0,25 g/cm <sup>3</sup>
Dimension	200mm x 120mm x 60mm (w x l x h)
Expansion ratio (loaded)	approx. 1:2
Expansion temperature	approx. 150°C
Environmental compatibility	solvent-free, no odour, environmentally friendly

## Test Certificates / Approvals

- ⇒ EN 1366-3 (cable/cable bundles, non combustible pipes)
- ⇒ ÖNORM B 3807 (EN 13501-2/classification reports)

## Packaging

- ⇒ 16 pieces per carton; 640 pieces per pallet
- Subject to change!

## Storage requirements

- ⇒ Store in cool and dry conditions
- ⇒ Shelf life at least 12 months

## Safety Instructions

- ⇒ Keep out of reach of children
- ⇒ Avoid contact with food and beverages
- ⇒ Please refer to the safety data sheet for additional advice