

## General

Intumex® PS fire stopping is a graphite-based pillow, which enables quick and easy, dust-free installation. Pillows that have previously been installed can be reused provided they have not been subjected to fire.

## Area of Application

Intumex® PS is a fire stopping pillow for walls and floors. It is designed for use with cables, cable trays and plastic pipes to seal against the spread of fire.

## System Advantages / Customer Benefits

- ⇒ Temporary penetration during construction and easy retro-fitting;
- ⇒ Permanent penetration at base of walls (smoke);
- ⇒ Dust proof, suitable for computer and server centres.

## Technical Data

Colour	light grey
Consistency	compact
Density	230 – 430 g/l
Solid content	100%
Reaction to fire	B1, slowly combustible
Expansion ratio	minimum 1:2.5 (30 mins. / 600°C)
Expansion temperature	approx. 150°C
Volume	Intumex® PS 750 approx. 2 l Intumex® PS 300 approx. 1 l
Dimensions	
Intumex® PS 750	approx. 320 x 200 mm
Intumex® PS 300	approx. 320 x 100 mm



## Test Certificate / Approval

- ⇒ EN 1366-3 (cable/cable bundles, pipes)
- ⇒ ÖNORM B 3807 (EN 13501-2/classification reports)
- ⇒ BS 476 Part 20
- ⇒ ASTM/UL

## Packaging

- ⇒ Intumex® PS 300 – 10 pieces per carton
  - ⇒ Intumex® PS 750 – 5 pieces per carton
- Subject to change!

## Storage requirements

- ⇒ Store in cool and dry conditions

## Safety Instructions

- ⇒ Keep out of reach of children
- ⇒ Avoid contact with food
- ⇒ Please refer to our safety data sheet for further precautions