



Intumex® Wrap - Fire stopping wrap



General description

Intumex® Wrap is an expanding fire stopping tape. Flexibility is given by the possibility to make any wrap diameter on site. Furthermore, it is the most space-efficient solution for plastic pipe penetrations.

Field of application

Intumex® Wrap is tested for walls and floors for soft and mortarsystem penetrations and for all common plastic piping materials, such as PVC, PE, PP; sound reduction drain pipes with multi layer technology and insulated aluminium composite as well as metal pipes.

System advantage / customer benefit

- ⇒ Flexible
- ⇒ Quick and easy installation
- ⇒ Resistant to atmospheric influences (light, heat, frost, UV radiation, humidity)
- ⇒ Universally usable

Test certificate / approval

- ⇒ EN 1366-3
- ⇒ EN 13501-1/2
- ⇒ ETAG 026-1/2

Packaging

- ⇒ Coil length: 18 m/box
- ⇒ 100 boxes/pallet
- Subject to change

Storage requirements

- ⇒ Store in cool and dry conditions

Safety instructions

- ⇒ Please refer to the safety information sheet for additional advice

Technical Data and Properties	
Colour	anthracite grey
Consistency	flexible wrap
Expansion temperature	approx. 150 °C
Thickness	approx. 2.5 mm
Width	approx. 50 mm
Use category	Class X
Reaction to fire	Class E
VOC content	< 0.01 g/l

